

XDS-1078-A9

Advanced 10.1" Interactive Room Panel

Industry's First Android 9.0 Meeting Room Panel — Highly Responsive & Secure



Android 9
By Google

Latest OS from Google.
Continuous security updates for reliability



PoE+ / PoE

Minimalist installation keeps workplaces simple & modern



2.8 cm Slim Design

Built-in zero-gap flush for secure, versatile mounting




High Visibility Status Light

Elegant light bars with soft illumination that is easy on the eyes



Orientation Aware

Easy to integrate into workplace design in portrait and landscape



High Performance Processor

Powers smooth, responsive, and vibrant user experience



10-Point Multi-Touch

Quick check-in/out or book room at-the-door. Zoom and scroll for easy browsing



Remote Device Management

Easily manage, monitor & troubleshoot all in-service room panels

Technical Specifications

Display

- 10.1" LCD panel
- 10 points capacitive multi-touch
- 300 nits maximum brightness
- 1280 x 800 panel resolution
- Viewing angle (H/V): 170 / 170
- 6 Primary colors LED side bar x 2

Internal Player

- Processor: Cortex-A53 Octa-core
- System memory: 2.0 GB
- Flash memory: 16 GB eMMC built-in

Connectivity

- Wi-Fi: 802.11 b/g/n
- Micro USB for ADB
- Ethernet RJ45: 10/100BASE-T
- USB 2.0 x 2
- Built-in 1W stereo speaker x 2
- 3.5 mm analog stereo audio out
- Optional 3G / 4G mobile module via USB
- Micro SD card slot, memory expandable to 16 GB / 32 GB / 64 GB (card replaces internal storage)

Room Management Software

- ResourceXpress room screen licence required

Advanced Features

- ResourceXpress remote device management
- Device health/connectivity monitoring
- Central management of location based settings
- MAC Address validation security
- Touchless interactive operation
- Equipment fault reporting

Supplied Accessories

- HW QSG
- Built-in VESA compatible 75 mm x 75 mm posts
- Back cover screws x 2 pcs
- Flush mount back cover

Optional Accessories

- Power adapter
- Expansion port connector
- Premium Wall Mount

Power Requirement

- Input: 100 - 200 V, 50 – 60 Hz
- Output: 12 V, 1.5 A
- UL / CB certified power supplies
- Interchangeable connector system includes
- US plug (optional for EU, UK, and AUS plugs)
- IEEE 802.3 at Power-over-Ethernet (PoE+)

Environmental

- Operating temperature: 0 to 40 °C
- Humidity: 10 to 85 % @ 40 °C non-condensing

Dimensions for Product & Package

- System Dimension: 270 mm x 171 mm x 28.5 mm (10.62" x 6.72" x 1.12")
- System Weight: 727g
- Individual package size: 336 mm x 100 mm x 227 mm
- Outer carton size: 523mm (W) x 356mm (D) x 259mm (H)
- Units per outer carton: 5 pcs

Certifications

- CE / FCC/RoHS

Warranty

- 1-year limited parts & labor (optional three years advance replacement available with ResourceXpress Warranty Plus)



USA

ResourceXpress Inc, 709 Silver Palm Avenue (unit i), Melbourne, FL 32901

Tel: +1-201 256 1601
Email: ussales@qedas.com

www.ResourceXpress.com

UK

QED ResourceXpress, 22 Bridgwater Court, Weston-super-Mare, BS24 9AY

Tel: +44 (0)1934 836960
Email: sales@qedas.com