



# RX-TD-360 Smart Desk Booking Panel

In a world where hybrid workspaces are the norm, desk booking becomes more than just a task, it's a strategy. Our sleek device, with its small form factor is the perfect solution for managing flexible workspaces. No more searching in vain or grappling with inefficiencies; reap the rewards with the industry's latest Android OS, a vivid multi-touch display, dual-band WiFi support, and enterprise security. Dive into an era where technology meets practicality.



Android 12



3.6" Multi-Touch Display



Splash Resistant



WiFi 5 & 802.1X



Dynamic Status LEDs



RFID (NFC) & Apple Wallet



Fortify+ Security



Flex-Mount & Cabling

- ❖ Clear indication of workspace status and availability
- ❖ Centrally managed server, fully scalable for enterprise-wide solutions
- ❖ Works with MS Outlook/Exchange, MS Office 365 Google Calendars and a wide range of advanced booking systems
- ❖ Instant desk booking, Check In/Out/Extend for true resource usage reporting
- ❖ Manages booking no shows, freeing up desks for others to use

- ❖ Supports optional authenticated access
- ❖ Touchless booking/Check in/Out/Extend
- ❖ Auto ring-fencing capabilities
- ❖ Reverse hoteling to free up semi-permanent resources to the bookable pool
- ❖ Set up and clean down policy booking
- ❖ Search and book using the RX Mobile app for iOS or Android devices

# RX-TD-360 Technical Specifications



System	OS	Android 12
	CPU	Quad-Core ARM Cortex-A35
	GPU	Mali-G31 MP2
	Memory	2GB
	Storage	16GB eMMC
	NFC / RFID	Opt.1: 13.56MHz Opt.2: 13.56MHz & 125KHz (Ver. H) Opt.3: Apple wallet compatible (Ver. O)
	Video decoder	H.265,H.264,VC-1, MPEG-1/2/4, VP8
	Image codecs	JPEG/PNG (Max. 1920 x 1080)
Display	Size(inch)	3.6", on-cell Multi-Touch
	Display Resolution	480 x 480
	Color	16.7M
	Viewing angle (H/V)	170/170 degree
	Brightness	350 nits
	Orientation display	Landscape / Portrait
I/O Interface ( External )	USB type C	x1, Power-In
	Micro USB	x1, ADB function
	LED light indicator	x2, 256 colors(1 x front, 1 x rear)
Power & Connectivity	RF communication	WiFi 5
	Power input	5V/2A
Mechanical	Dimension (WxDxH) (mm / inch) (Estimated)	90 mm x 90 mm x 13mm (3.54"x 3.54" x 0.51")
	Net. Weight (Estimated)	130g
	Weight with packing (Estimated)	180g
	Mounting type	Glass / Surface / Wall
	Material	PC
Environment	Operating Temperature(°C)	0~40°C
	Storage Temperature (package included) (°C)	-20°C to 60°C
	Ambient Relative Humidity	0 to 90% (non-condensing)
Certification & Safety	Certification	CE/UKCA/FCC/IMDA/CB
	Green	RoHS / REACH
Warranty	Warranty Period	1 year
Accessory	Screw	Yes
	Bracket	Yes
	Tape	Yes
	QSG	Yes
	Desktop stand	Optional