

Technical Specifications

- 21.5" IPS LCD panel
- 10 points capacitive multi-touch
- 250 nits maximum brightness
- 1920 x 1080 (Full HD) panel resolution
- Viewing angle (H/V): 178/178

- Processor: Cortex-A17 1.8 GHz Quad-Core
- System memory: 2.0 GB
- Flash memory: 8 GB eMMC built-in

- H.264/AVC up to 1080p (1920 x 1080)
- H.265/AVC up to 1080p (1920 x 1080)
- MPEG-4 up to 1080p (1920 x 1080)
- MPEG-2 up to 1080p (1920 x 1080)
- MPEG-1 up to 1080p (1920 x 1080)
- VC-1 up to 1080p (1920 x 1080)

- JPEG up to 1920 x 1080
- PNG up to 1920 x 1080

- MP3 up to 320 Kbps

- 

- Widgets for calendar, clock, news, and web page integration
- HTML5 technologies including CSS and Javascript
- Chromium-based browser engine, same as Google Chrome™

- Front camera: 2MP
- Wi-Fi: 802.11 b/g/n
- Mini USB for ADB (Android Debug Bridge)
- Ethernet RJ45
- USB 2.0 x 3
- Built-in stereo speakers 2 W x 2
- 3.5 mm analog stereo audio out
- SD card slot, memory expendable to 16 GB / 32 GB / 64 GB (card replaces internal storage)


- Built-in VESA MIS-D 100 mm x 100 mm mounting points

- HTML5, JavaScript, and CSS
- W3C SMIL for cross-platform management
- W3C widgets for HTML delivery
- Android 7.1 API

- Power adapter
- Power cord
- I/O bracket
- Quick guide

- Adjustable table stand (PVK-302)



- Input: AC 100 - 240 V, 50 - 60 Hz, 1.5 A max
- Output: 12 V / 3 A
- 


- Operating temperature: 0 to 40 °C
- Humidity: 10 to 85 % @ 45 °C, non-condensing

- System dimension: 538 mm x 331 mm x 37 mm (21.18" x 13.03" x 1.46")
- System weight: 3.83 kg (8.44 lbs)
- Package weight: 5.8 kg (12.78 lbs)

- CE / FCC / RoHS

- 1-year limited parts & labor* (varies based on region, contact sales for more details)

Universal I/O Port for Extension



USA
ResourceXpress Inc, 709 Silver Palm Avenue (unit i), Melbourne, FL 32901

Tel: +1-201 256 1601
Email: ussales@qedas.com

UK
QED ResourceXpress, 22 Bridgwater Court, Weston-super-Mare, BS24 9AY

Tel: +44 (0)1934 836960
Email: sales@qedas.com